

- All plastic ultra light weight versions
- Sintered metal
- All metal versions for heavy duty applications
- Versions with push-in connections
- High noise level reduction
- Low back pressure generation
- Restrictor silencers screw adjustment



Operating and additional information

Plastic	Working temperature:	-10°C to +80°C		
	Efficiency	92%		
Metal	Working temperature:	-10°C to +74°C	Working pressure	up to 17 bar

Push-in Series



Port mm	Order code
4	PXC-X14
6	PZC-S1006
8	PZC-S1008

Sintered Bronze Series (female)



Port mm	Order code
G1/8	9721900404

Sintered Metal Series



Port thread	Order code
R1/8	04502R0002
R1/4	04504R0004
R3/8	04506R0060
R1/2	04508R0008
R3/4	04512R0012
R1	04516R0016

Sintered Stainless Steel Series



Port thread	Order code
G1/8	9126900195
G1/4	9126900196

Self Cleaning, 48 Series



Port thread	Order code
R1/8	ESB12MC
R1/4	ESB25MC
R3/8	ESB37MC
R1/2	ESB50MC
R3/4	ESB75MC
R1	ESB100MC
R1-1/4	ESB125MC
R1-1/2	ESB150MC

Heavy Duty Series



Port thread	Order code
G3/8	P6M-MA13
G1/2	P6M-MA14
G3/4	P6M-MA16
G1	P6M-MA18