

Pneumatic Ball Valves & Action Valves

7913 Mini Ball Valves, 3/2 version, with vent, with push-in connection



ØD	Order code
4	7913 04 00
6	7913 06 00
8	7913 08 00
10	7913 10 00
12	7913 12 00

7914 Mini Ball Valves 3/2 version, with vent, with BSPP thread & push-in connection



ØD	C	Order code
6	G1/8	7914 06 10
8	G1/4	7914 08 13
10	G3/8	7914 10 17
12	G1/2	7914 12 21

7910 Mini Ball Valves, 2/2 version, with push-in connection



ØD	Order code
4	7910 04 00
6	7910 06 00
8	7910 08 00
10	7910 10 00
12	7910 12 00

7911 Mini Ball Valves, 2/2 Version with BSPP thread & push-in connection



ØD	C	Order code
6	G1/8	7911 06 10
8	G1/4	7911 08 13
10	G3/8	7911 10 17
12	G1/2	7911 12 21

0492 Double Female



-20° to +80°C
12 bar

C	DN	Order code
G1/4	4	0492 04 13
G1/4	4	0492 04 13 64
G3/8	7	0492 07 17
G1/2	10	0492 10 21
G3/4	13	0492 13 27

0491 Male & Female, BSPP



-20° to +80°C
12 bar

C	DN	Order code
G1/4	4	0491 04 13
G1/4	4	0491 04 13 64
G3/8	7	0491 07 17
G1/2	10	0491 10 21
G3/4	13	0491 13 27

0402 Standard In-Line Ball Valve - Double Female, BSPP



-20° to +80°C
40 bar

C	DN	Order code
G1/8	4	0402 04 10
G1/8	7	0402 07 10
G1/4	7	0402 07 13
G3/4	10	0402 10 17
G1/2	13	0402 13 21
G3/4	20	0402 20 27
G1"	23	0402 23 34

0401 Standard In-Line Ball Valve, Male Female BSPP



-20° to +80°C
40 bar

ØD	C	Order code
4	G1/8	0401 04 10
7	G1/4	0401 07 13
10	G3/8	0401 10 17
13	G1/2	0401 13 21
18	G3/4	0401 18 27
23	G1"	0401 23 34

4902 In-Line Ball Valves, Fluoropolymer Series, BSPP




-20° to +130°C
30 bar


C	DN	PN	Order code
G1/4	10	30	4902 10 13
G3/8	10	30	4902 10 17
G1/2	15	30	4902 15 21
G3/4	20	30	4902 20 27
G2.1/2	25	30	4902 25 34
G2.1/2	32	30	4902 32 42
G2.1/2	40	30	4902 40 49
G2.1/2	50	30	4902 50 48
G2.1/2	65	30	4902 65 47
G3"	80	30	4902 80 46
G4"	100	30	4902 01 45

Pneumatic Ball Valves & Action Valves


0439 Lockable Ball Valves, Double Female with vent, BSPP

 -20° to +80°C 40 bar	ØD	C	Order code
	4	G1/8	0439 04 10
7	G1/4	0439 07 13	
10	G3/8	0439 10 17	
13	G1/2	0439 13 21	
18	G3/4	0439 18 27	
23	G1"	0439 23 34	


0469 Double Female Vented Ball Valves BSPP

 -20° to +80°C 40 bar	ØD	C	Order code
	4	G1/8	0469 04 10
7	G1/4	0469 07 13	
10	G3/8	0469 10 17	
13	G1/2	0469 13 21	
18	G3/4	0469 18 27	
23	G1"	0469 23 34	


0448 Panel Mountable Female, BSPP, right angle porting

 -20° to +80°C 40 bar	ØD	C	Order code
	4	G1/8	0448 04 10
6	G1/4	0448 06 13	
9	G3/8	0448 09 17	
12	G1/2	0448 12 21	

4810 Ball Valve, Double Female BSPP


	C	DN	PN	Order code
	G1/4	8	64	4810 08 13
G3/8	10	64	4810 10 17	
G1/2	15	64	4810 15 21	
G3/4	20	40	4810 20 27	
G1"	25	40	4810 25 34	

0438 Female, 3 port 2 way Lockable Ball Valve, BSPP


 -20° to +80°C 40 bar	ØD	C	Order code
	9	G3/8	0438 09 17
12	G1/2	0438 12 21	
18	G3/4	0438 18 27	
23	G1"	0438 23 34	

The Ball Valves, Universal Series, can be adapted to various applications in semi-standard versions.

0489 In-Line Vented Ball Valves, BSPP, with threaded exhaust

 -20° to +80°C 40 bar	ØD	C	Order code
	7	G1/4	0489 07 13
10	G3/8	0489 10 17	
13	G1/2	0489 13 21	
18	G3/4	0489 18 27	
23	G1"	0489 23 34	

0449 In-Line Vented Ball Valves, BSPP, panel mountable

 -20° to +80°C 40 bar	ØD	C	Order code
	7	G1/4	0449 07 13
10	G3/8	0449 10 17	
13	G1/2	0449 13 21	