

Pneumatic Accessories

0670 Threaded Silencer, BSPP



-20° to +150°C
12 bar

C	Order code
G1/8	0670 00 10
G1/4	0670 00 13
G3/8	0670 00 17
G1/2	0670 00 21
G3/4	0670 00 27
G1	0670 00 34

0673 Threaded Silencer, Male BSPP & M5



-20° to +150°C
12 bar

C	Order code
M5 x 0.8	0673 00 19
G1/8	0673 00 10
G1/4	0673 00 13
G3/8	0673 00 17
G1/2	0673 00 21

0672 Flow-Control Silencer, Male BSPP



-20° to +150°C
12 bar

C	Order code
G1/8	0672 00 10
G1/4	0672 00 13
G3/8	0672 00 17
G1/2	0672 00 21

0674 Threaded Silencer, Male BSPP & M5



-10° to +80°C
10 bar

C	Order code
M5 x 0.8	0674 00 19
G1/8	0674 00 10
G1/4	0674 00 13
G3/8	0674 00 17
G1/2	0674 00 21
G3/4	0674 00 27
G1	0674 00 34

0677 Silencer, Miniature, BSPP



-20° to +150°C
12 bar

C	Order code
G1/8	0677 00 10
G1/4	0677 00 13
G3/8	0677 00 17
G1/2	0677 00 21
G3/4	0677 00 27
G1	0677 00 34

Technical specifications of aluminium anodised manifolds

-10°C to +80°C
20 bar max.

0605 Fluoropolymer Tape



-250° to +260°C

Order code
0605 12 12

3311 Female Manifold BSPP & M5



C1	C2	Number of Outlets	Order code
G1/8	M5 x 0.8	7	3311 19 10 07
G1/4	G1/8	2	3311 10 13 02
G1/4	G1/8	3	3311 10 13 03
G1/4	G1/8	4	3311 10 13 04
G1/4	G1/8	5	3311 10 13 05
G1/4	G1/8	6	3311 10 13 06
G3/8	G1/4	2	3311 13 17 02
G3/8	G1/4	3	3311 13 17 03
G3/8	G1/4	4	3311 13 17 04
G3/8	G1/4	5	3311 13 17 05
G3/8	G1/4	6	3311 13 17 06

3313 Double Female Manifold BSPP



C1	C2	Number of Outlets	Order code
G1/4	G1/8	2	3313101302
G1/4	G1/8	3	3313101303
G1/4	G1/8	4	3313101304
G1/4	G1/8	5	3313101305
G3/8	G1/4	2	3313131702
G3/8	G1/4	3	3313131703
G3/8	G1/4	4	3313131704
G3/8	G1/4	5	3313131705
G1/2	G1/4	3	3313132103
G1/2	G1/4	4	3313132104
G1/2	G1/4	5	3313132105

3312 Female Cross Manifold BSPP & M5



C	Order code
M5 x 0.8	3312 00 19
G1/8	3312 00 10
G1/4	3312 00 13
G3/8	3312 00 17
G1/2	3312 00 21