


Rectus Series 126KA - DN 7.2

Universal brass coupling with European standard industrial profile. Coupling system with single-handed operation and standard-valve. Series 26 plugs in brass. Series 25 steel plugs recommended for oscillating forces.

Chart / Air



Advantages

- Compact outer dimension
- High working pressure
- Optimized flow rate



Working Pressure

PB = 40 bar, maximum static working pressure with safety factor of 4 to 1.

Working Temperature*

-20°C up to +100°C (NBR) depending on the medium.

*At a temperature below -20°C and above +100°C special seals are available on request.

Material

Coupling

Back Body	Brass
Valve Body	Brass
Sleeve	Brass
Valve	Brass
Spring and Locking Ring	AISI 303
Locking Balls	AISI 420
Seals	NBR

Plug

Brass

Coupling - Male Thread BSPT

Thread A	Order code	Box Qty
1/4"	126KAAW13MPX	20
3/8"	126KAAW17MPX	20
1/2"	126KAAW21MPX	20

Plug - Male Thread BSPP

Thread A	Order code	Box Qty
1/4"	26SFAW13MXX	20
3/8"	26SFAW17MXX	20
1/2"	26SFAW21MXX	20

Coupling - Female Thread BSPP

Thread A	Order code	Box Qty
1/4"	126KAIW13MPX	20
3/8"	126KAIW17MPX	20
1/2"	126KAIW21MPX	20

Plug - Female Thread BSPP

Thread A	Order code	Box Qty
1/4"	26SFIW13MXX	20
3/8"	26SFIW17MXX	20
1/2"	26SFIW21MXX	20

Coupling - Hose Barb

Thread A	Order code	Box Qty
6 mm	126KATF06MPX	20
8 mm	126KATF08MPX	20
9 mm	126KATF09MPX	20
10 mm	126KATF10MPX	20
13 mm	126KATF13MPX	20

Plug - Hose Barb

Thread A	Order code	Box Qty
6 mm	26FTF06MXX	20
8 mm	26FTF08MXX	20
9 mm	26FTF09MXX	20
10 mm	26FTF10MXX	20
13 mm	26FTF13MXX	20